



316L Flex Chimney Liner Packs - TecnoFlex Plus



TecnoFlex has a number of features:

- Unique joint design giving exceptional strength to the lock.
- Both inner and outer layers made from corrosion-resistant 316L stainless steel.
- Corrugated outer skin for high crush resistance.
- Extra smooth inner skin allows for easy drain down of condensates, less opportunity for soot to collect in the joint area and ease of sweeping.
- Inner skin remains smooth and protective even after the rigours of installation.

VARIATIONS

SKU	Int mm	Pack Length (m)	Price
125021	125	15	
128142	250	05	
128143	250	06	
128144	250	07	
128145	250	08	
128146	250	09	
128653	300	06	
128654	300	07	
126415	155	40	
125030	125	40	
124509	100	40	
127126	200	30	
126545	180	30	
126413	155	30	
125028	125	30	
124507	100	30	



SKU	Int mm	Pack Length (m)	Price
130467	080	30	
127114	200	12	
124490	100	12	
130461	080	12	
125010	125	12	
126398	155	12	
126532	180	12	
127113	200	11	
126531	180	11	
126397	155	11	
125006	125	11	
127112	200	10	
126530	180	10	
126396	155	10	
125002	125	10	
126553	180	09	
124633	100	10	
130457	080	10	
127132	200	09	
126423	155	09	
125054	125	09	
124647	100	09	
130498	080	09	
127131	200	08	
126552	180	08	
126422	155	08	
125049	125	08	
124524	100	08	
130497	080	08	
127130	200	07	
126551	180	07	
125045	125	07	
126550	180	06	
127129	200	06	
124520	100	07	
126421	155	07	
126420	155	06	
125040	125	06	
124516	100	06	
130493	080	06	
127128	200	05	



SKU	Int mm	Pack Length (m)	Price
126549	180	05	
126418	155	05	
125034	125	05	
124511	100	05	
128138	250	10	
128140	250	12	
155944	250	13	
128651	300	10	

PRODUCT DESCRIPTION

Flexible Flue Twin Wall Liner

TecnoFlex Plus is a twin skin flexible chimney liner designed for gas, oil and multi-fuel, where the maximum flue gas temperature does not exceed 600°C. Diameter range 80 - 300mm. Flex Liners come with a Lifetime Guarantee*

- Corrugated outer skin for high crush resistance.
- Extra smooth inner skin allows for easy drain down of condensates, less opportunity for soot to collect in the joint area and ease of sweeping.
- Engineered joint design gives extra strength and flexibility.
- Inner skin remains smooth and protective even after the rigours of installation.
- Now with Lifetime*Guarantee.



For stove and chimney installers – whenever you register an installation with our easy to use, online guarantee registration portal, you will now accrue points based on the number of installations and installation type. So start to register your installations, taking full advantage of our Lifetime Guarantee on Flex and ICID, as well as guarantees on all our other ranges, and to start earning points



TecnoFlex
DOPs and [Download](#)
[certificates](#)



Triplelock
DOPs and [Download](#)
[certificates](#)



XD DOPs
and [Download](#)
[certificates](#)

**TecnoFlex
Plus is CE
Certified to
BS
EN1856-2
TÜV 0036
CPR 9195
035 with
designation**



SCHIEDEL CHIMNEY SYSTEMS LTD.
PRODUCT TECHNICAL DATA SHEET



S:

High Temperature Applications

T600 N1 W V2 L50012 G

T600 N1 W V2 L70012 G

Low Temperature Applications

T200 P1 W V2 L50012 O

T200 P1 W V2 L70012 O

Triplelock Plus is CE Certified to BS EN1856-2 TÜV 0036 CPR 9195 043 with designations:

Applications

T300 N1 W V2 L50010 O



Flexible
Liners
brochure

[Download](#)



Flexible
Liners
installation
instructions

[Download](#)

A useful app with guides on installation as well as step-by-step video guides.

This app was designed for installers to have all the information they require in a few quick clicks. This makes it easier for installers rather than having to carry paperwork during the installation process with video breakdowns of each stage of the installation process.

Download the iPhone and iPad version in the App Store and Android version in the Google Play Store.

