



CHIMNEY PLATE

CE	SCHIEDEL CHIMNEY SYSTEMS
IMPORTANT SAFETY INFORMATION THIS NOTICE MUST NOT BE REMOVED OR COVERED	
PROPERTY ADDRESS: <u>Sunila College, Truroville</u>	
THE CHIMNEY SYSTEM IS INSTALLED IN THE: <u>Lounge</u>	
SYSTEM IS SUBSTITUTION: SOLID FUEL <input type="checkbox"/> GAS <input type="checkbox"/> OIL OR M.O. <input type="checkbox"/> OTHER <input type="checkbox"/>	
APPLIANCE IS CONDENSING: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> INTENTIVE OF REAL FITTED: SOLID GAS <input type="checkbox"/> SOLID OIL <input type="checkbox"/>	
APPLIANCE INSTALLED IN: <u>Wood burning stove</u>	
FLUE TYPE:	
TRIMBLOCK <input type="checkbox"/>	TECHNOLOG PLUS <input checked="" type="checkbox"/>
ICID <input type="checkbox"/>	ICID <input type="checkbox"/>
ACT <input type="checkbox"/>	ACT <input type="checkbox"/>
DATE OF INSTALLATION: <u>10/05/18</u>	APP. JOB NO.: <u>19918</u>
INSTALLER NAME(S): <u>A.N. Snelaker, Steve Gilman, Christopher Tyle and Mark NESSONS</u>	
OTHER INFORMATION: <u>Flex Liner</u>	
CHIMNEY DESCRIPTION: <u>T600 N2 D 3 G</u>	
PLATE REF: <u>155444</u>	
<p>IMPORTANT! PLEASE ENSURE THAT THE APPLIANCE IS CREATED IN ACCORDANCE WITH THE MANUFACTURERS RECOMMENDATIONS IT IS ADVISED THAT THE SYSTEM IS REGULARLY INSPECTED IN ACCORDANCE WITH THE INSTALLATION INSTRUCTIONS TO ENSURE THAT THE SYSTEM OPERATES PROPERLY.</p> <p>PLEASE ENSURE THAT ALL THE INFORMATION IS FILLED IN WITH THE USE OF PERMANENT INK.</p>	

This product is part of the Schiedel range of Ceramic Flue Liners, which have been tested and approved to meet the latest European Standards and Construction Product Regulations (CPR) for both High Temperature and Low Temperature applications.

PRODUCT DESCRIPTION

ACPLATE2002 CHIMNEY PLATE

For stove and chimney installers – whenever you register an installation with our easy to use, online guarantee registration portal, you will now accrue points based on the number of installations. So [click here](#) to start and register your installations, taking full advantage of our Lifetime Guarantee on Flex and ICID, as well as guarantees on all our other ranges, and to start earning points

[wprm_package id='47854']

Isokern Pumice Double Module DM is CE Certified to EN1858 TÜV Cert no. 0036 CPR 90219 001
Isokern Pumice Chimney Liner is CE certified to EN1857 TÜV Cert no. 0036 CPR 90219 002
Isokern Magnum Firechest has been tested at the Fraunhofer Institut, Stuttgart, Cert no. P8-094/2006

CE Designation

Double Module DM System Chimney* T450 N1 D 3 G(00)
Pumice Chimney Liner T600 N2 D 3 G

* Zero distance to combustibles on straight chimney systems with ventilated terminal. 38mm distance to combustibles on offset systems. and non ventilated systems.

[Isokern brochure](#)

[Magnum Firechest instructions](#)

[Click here](#) to view Certificates and Declarations of Performance for Isokern DM

A useful app with guides on installation as well as step-by-step video guides.



SCHIEDEL CHIMNEY SYSTEMS LTD.
PRODUCT TECHNICAL DATA SHEET



This app was designed for installers to have all the information they require in a few quick clicks. This makes it easier for installers rather than having to carry paperwork during the installation process with video breakdowns of each stage of the installation process.

Download the iPhone and iPad version in the App Store and Android version in the Google Play Store.

