

# SCHIEDEL CHIMNEY SYSTEMS LTD. PRODUCT TECHNICAL DATA SHEET



### Combined Screwfit Pot Hanger and Terminal - Flexible Liners





This updated design of the Pot hanger in the key  $\emptyset$ 125 and  $\emptyset$ 155 diameters brings additional strength with mesh included as standard; one piece looped straps fasted with bolts to the terminal cap and spot welded to the mesh, and Schiedel's tested and approved screwfit design ensuring that this pot hanger and terminal can bear the weight of up to 15m of TecnoFlex Plus liner.

The product is supplied complete with a screw band and jubilee clip fastening to allow for fixing to the existing chimney pot #MakingLifeSimple

Features	Benefits	
Screwfix design with inner liner.	Designed to fit the pitch of TecnoFlex Plus products. Tested & approved to take load of up to 15m of TecnoFlex Protects flex & ensures rainwater remains inside the liner.	
One piece spinning for the base plate and upstand.	Deflects rain Prevents water ingress to outside of flex.	
Bolt fixing on top cap.	Gives added strength & wind resistance.	
316L stainless steel including mesh.	High Corrosion-resistance.	
Lightweight and robust.	Simple and fast to install, and load bearing.	

### **VARIATIONS**

SKU	Int mm	Colour	Price
175441	125	Plain	
175443	155	Plain	
175444	125	Terracotta	
175446	155	Terracotta	

### **PRODUCT DESCRIPTION**



# SCHIEDEL CHIMNEY SYSTEMS LTD. PRODUCT TECHNICAL DATA SHEET



TecnoFlex Plus is a twin skin flexible chimney liner designed for gas, oil and multi-fuel, where the maximum flue gas temperature does not exceed 600°C. Diameter range 80 - 300mm. Flex Liners come with a Lifetime Guarantee\*

#### Flexible Flue Twin Wall Liner

- Corrugated outer skin for high crush resistance.
- Extra smooth inner skin allows for easy drain down of condensates, less opportunity for soot to collect in the joint area and ease of sweeping.
- Engineered joint design gives extra strength and flexibility.
- Inner skin remains smooth and protective even after the rigours of installation.
- Now with Lifetime\*Guarantee.

Triplelock Plus is a single wall stainless steel flexible flue liner designed for atmospheric gas and kerosene appliances where the flue gas temperature does not exceed 260°C. Diameter range Triplelock plus 100 - 200mm.


### Flexible Flue Single Wall Liner

- Made from corrosion-resistant 316L stainless steel.
   Leak resistant construction due to dovetail folded seam.
- Deep corrugations for high crush resistance and better flexibility when installing.
- Strong seam construction resists the rigours of pulling the liner into place during construction.



For stove and chimney installers – whenever you register an installation with our easy to use, online guarantee registration portal, you will now accrue points based on the number of installations and installation type. So start to register your installations, taking full advantage of our Lifetime Guarantee on Flex and ICID, as well as guarantees on all our other ranges, and to start earning points







TecnoFlex Plus is CE Certified to BS EN1856-2 TÜV 0036 CPR 9195 035 with designation s:

High Temperature Applications T600 N1 W V2 L50012 G T600 N1 W V2 L70012 G

**Low Temperature Applications** T200 P1 W V2 L50012 O



# SCHIEDEL CHIMNEY SYSTEMS LTD. PRODUCT TECHNICAL DATA SHEET




T200 P1 W V2 L70012 O

Triplelock Plus is CE Certified to BS EN1856-2 TÜV 0036 CPR 9195 043 with designations:

### **Applications**

T300 N1 W V2 L50010 O





A useful app with guides on installation as well as step-by-step video guides.

This app was designed for installers to have all the information they require in a few quick clicks. This makes it easier for installers rather than having to carry paperwork during the installation process with video breakdowns of each stage of the installation process.

Download the iPhone and iPad version in the App Store and Android version in the Google Play Store.



