



Condensate collector with side drain - MEKA



Condensate collector with side drain - MEKA is part of the Schiedel ME range, which has a number of applications and advantages.

APPLICATIONS

- Shaft liner in renovation projects
- Air inlet & ventilation systems
- Flue system for condensing heaters and boilers
- Chimney renovation

ADVANTAGES

- Stress free thermal expansion
- Can be connected to MF flue system
- High quality stainless steel system
- High temperature silicone sealing ring
- Universal application
- Light weight system
- Chimney fire resistant

VARIATIONS

| SKU | Int mm | Colour | Price |
|--------|--------|--------|-------|
| 161224 | 080 | Plain | |
| 161225 | 100 | Plain | |
| 161226 | 113 | Plain | |
| 161227 | 130 | Plain | |
| 161228 | 150 | Plain | |
| 161229 | 180 | Plain | |
| 161230 | 200 | Plain | |
| 161231 | 250 | Plain | |
| 161232 | 300 | Plain | |
| 161233 | 350 | Plain | |
| 161234 | 400 | Plain | |



| SKU | Int mm | Colour | Price |
|--------|--------|--------|-------|
| 161235 | 450 | Plain | |
| 161236 | 500 | Plain | |

PRODUCT DESCRIPTION

ME system is a modular single wall flue/chimney system, made of stainless steel with a silicone sealing ring.

ME is a universal flue/chimney system which is suitable for both high and low temperatures, non-condensing and condensing applications with flue gasses under positive and negative pressure. It can resist a chimney fire.

Therefore the system is suitable for a wide range of applications such as boilers, stoves, ovens and a ventilation system. The system can also be used for CHP applications, in this case a special VITON® sealing ring might be necessary.

Technical characteristics

| | |
|----------------------------|--|
| Application | System Chimney/Connecting Flue Pipe/Chimney Liner |
| Operating mode | Dry/wet |
| Pressure | N1/P1/H1 |
| Max. working pressure | 5000 Pa |
| Max. operating temperature | 600°C (negative pressure - N1 applications) 200°C (positive pressure - P1/H1 applications) |
| Soot Fire Resistant* | Yes (see G designations below) No (see O designations below) |
| Inner wall material | AISI 316L/EN 1.4404 |
| Inner wall thickness | Ø80 - Ø200: 0.4mm Ø250 - Ø300: 0.5mm Ø350: 0.6mm |
| Fuel type | Oil/wood/coal/pellets normal (wood)/gas |
| Sealant | Elastomer. (Where case flue gas temperatures exceed 200°C, sealants as well as the cap and door seals should be removed before installation) |

For stove and chimney installers – whenever you register an installation with our easy to use, online guarantee registration portal, you will now accrue points based on the number of installations. So [click here](#) to start and register your installations, taking full advantage of our Lifetime Guarantee on Flex and ICID, as well as guarantees on all our other ranges, and to start earning points

[ME International brochure](#)

[Click here](#) to view Certificates and Declarations of Performance

CE approved | EN 1856-1: System Chimney

T200 P1/H1 W V2 L50050 O30

CE approved | EN 1856-2: Connecting Flue Pipe

T200 P1/H1 W V2 L50050 O30 M



T600 N1 D V2 L50050 G400 M

CE approved | EN1856-2: Chimney Liner

T200 P1/H1 W V2 L50050 O

T600 N1 D V2 L50050 G

* Above CE designations refer to Ø80-300 – For larger diameters please contact us.