



Extended Adaptor: Vitreous flue system to XD flexible liner



The Metaloterm® XD system is a single strip, smooth bore flexible flue system made of stainless steel.

Metaloterm® XD is suitable for both high and low temperatures, non-condensing and condensing applications with flue gases in positive and negative pressure conditions. Therefore the system is suited for a wide range of renovation situations to line an existing chimney.

Advantages include

- Chimney renovation
- Dimensional stability, even after multiple bending
- Marked every single metre
- Manufactured from austenitic stainless steel
- Connects with Metaloterm range


VARIATIONS




SKU	Flex	Ø Nom SW	Price
168846	125	122	

PRODUCT DESCRIPTION

Technical characteristics	
Application	Flue system/connecting flue/renovation
Operating mode	Dry/wet
Pressure	Negative/positive pressure
Max. working pressure	200 Pa
Operating temperature	200°C positive pressure
600°C negative pressure	
Max. temperature allowed	1000°C (max 30 min)
material	AISI 316L/EN 1.4404
AISI 904L/EN 1.4539	
thickness	0.1 mm
Fuel type	Oil/Gas/Wood/Pellets Normal (Wood)


[XD brochure](#) [Download](#)

 XD DOPs and certificates Download	Technical characteristics	
	Application	Flue system/connecting flue/renovation
Operating mode	Dry/wet	
Pressure	Negative/positive pressure	
Max. working pressure	200 Pa	
Operating temperature	200°C positive pressure	
600°C negative pressure		
Max. temperature allowed	1000°C (max 30 min)	
material	AISI 316L/EN 1.4404	
AISI 904L/EN 1.4539		



thickness

0.1 mm

Fuel type

Oil/Gas/Wood/Pellets Normal (Wood)