



Extended Adaptor: Vitreous flue system to XD flexible liner



The Metaloterm® XD system is a single strip, smooth bore flexible flue system made of stainless steel.

Metaloterm® XD is suitable for both high and low temperatures, non-condensing and condensing applications with flue gases in positive and negative pressure conditions. Therefore the system is suited for a wide range of renovation situations to line an existing chimney.

Advantages include

- Chimney renovation
- Dimensional stability, even after multiple bending
- Marked every single metre
- Manufactured from austenitic stainless steel
- Connects with Metaloterm range


VARIATIONS




| SKU | Flex | Ø Nom SW | Price |
|--------|------|----------|-------|
| 168846 | 125 | 122 | |

PRODUCT DESCRIPTION

| | |
|---------------------------|--|
| Technical characteristics | |
| Application | Flue system/connecting flue/renovation |
| Operating mode | Dry/wet |
| Pressure | Negative/positive pressure |
| Max. working pressure | 200 Pa |
| Operating temperature | 200°C positive pressure |
| 600°C negative pressure | |
| Max. temperature allowed | 1000°C (max 30 min) |
| material | AISI 316L/EN 1.4404 |
| AISI 904L/EN 1.4539 | |
| thickness | 0.1 mm |
| Fuel type | Oil/Gas/Wood/Pellets Normal (Wood) |


[XD brochure](#) [Download](#)

| | |
|---|--|
|  XD DOPs and certificates Download | Technical characteristics |
| | Application |
| | Flue system/connecting flue/renovation |
| Operating mode | Dry/wet |
| Pressure | Negative/positive pressure |
| Max. working pressure | 200 Pa |
| Operating temperature | 200°C positive pressure |
| 600°C negative pressure | |
| Max. temperature allowed | 1000°C (max 30 min) |
| material | AISI 316L/EN 1.4404 |
| AISI 904L/EN 1.4539 | |



thickness

0.1 mm

Fuel type

Oil/Gas/Wood/Pellets Normal (Wood)