



LOCKING\_BAND\_W\_SCREW 300/0.5/304/MA/ME



This product is part of the Schiedel Metaloterm ME range, which has a number of applications and advantages.

#### **APPLICATIONS**

- Shaft liner in renovation projects
- Air inlet & ventilation systems
- Flue system for condensing heaters and boilers
- Chimney renovation

#### **ADVANTAGES**

- Stress free thermal expansion
- Can be connected to Metaloterm® MF
- High quality stainless steel system
- High temperature silicone sealing ring
- Universal application
- Light weight system
- Chimney fire resistant

#### **PRODUCT DESCRIPTION**




The Metaloterm® ME system is a modular single wall flue/chimney system, made of stainless steel with a high temperature sealing ring. Metaloterm® ME is a universal flue/ chimney system which is suitable for both high and low temperatures, non-condensing, and condensing applications with flue gasses in positive and negative pressure.

It can resist a chimney fire. Therefore, the system is suited for a wide range of applications such as boilers, stoves, ovens and as ventilation system. It can be used as a connection flue pipe or in renovation situations as a shaft liner. The product range also contains a wide variety of silencers.

The system can also be used for CHP applications, in this case a special VITON® sealing ring might be necessary.



For stove and chimney installers – whenever you register an installation with our easy to use, online guarantee registration portal, you will now accrue points based on the number of installations and installation type. So start to register your installations, taking full advantage of our Lifetime Guarantee on Flex and ICID, as well as guarantees on all our other ranges, and to start earning points

 <a href="#">ME brochure</a> <a href="#">Download</a>	 <a href="#">ME DWG files</a> <a href="#">Download</a>
 <a href="#">ME DOPs and certificates</a> <a href="#">Download</a>	<p><b>CE approved   EN 1856-1: System Chimney</b></p> <p>T200 P1/H1 W V2 L50050 O30</p> <p><b>CE approved   EN 1856-2: Connecting Flue Pipe</b></p>
<p>T200 P1/H1 W V2 L50050 O30 M T600 N1 D V2 L50050 G400 M</p> <p><b>CE approved   EN1856-2: Chimney Liner</b></p> <p>T200 P1/H1 W V2 L50050 O T600 N1 D V2 L50050 G</p>	

\* Above CE designations refer to Ø80-300 – For larger diameters please contact us.