



Metaloterm XD 316 packs



The Metaloterm® XD system is a single strip, smooth bore flexible flue system made of stainless steel.

Metaloterm® XD is suitable for both high and low temperatures, non-condensing and condensing applications with flue gases in positive and negative pressure conditions. Therefore the system is suited for a wide range of renovation situations to line an existing chimney.

Advantages include

- Chimney renovation
- Dimensional stability, even after multiple bending
- Marked every single metre
- Manufactured from austenitic stainless steel
- Connects with Metaloterm range

VARIATIONS

SKU	Int mm	Pack Length (m)	Thickness	Steel Type	Price
168667	125	30	0.1	316	
168635	125	5	0.1	316	
168636	150	5	0.1	316	
168639	125	6	0.1	316	



SKU	Int mm	Pack Length (m)	Thickness	Steel Type	Price
168640	150	6	0.1	316	
168643	125	7	0.1	316	
168644	150	7	0.1	316	
168647	125	8	0.1	316	
168648	150	8	0.1	316	
168651	125	9	0.1	316	
168652	150	9	0.1	316	
168655	125	10	0.1	316	
168656	150	10	0.1	316	
168657	180	10	0.12	316	
168658	200	10	0.12	316	
168659	125	11	0.1	316	
168660	150	11	0.1	316	
168661	180	11	0.12	316	
168663	125	12	0.1	316	
168664	150	12	0.1	316	
168665	180	12	0.12	316	
168670	200	30	0.12	316	
168671	125	40	0.1	316	
168672	150	40	0.1	316	

PRODUCT DESCRIPTION

Technical characteristics

Application	Flue system/connecting flue/renovation
Operating mode	Dry/wet
Pressure	Negative/positive pressure
Max. working pressure	200 Pa
Operating temperature	200°C positive pressure
600°C negative pressure	
Max. temperature allowed	1000°C (max 30 min)
material	AISI 316L/EN 1.4404
AISI 904L/EN 1.4539	
thickness	0.1 mm
Fuel type	Oil/Gas/Wood/Pellets Normal (Wood)



SCHIEDEL CHIMNEY SYSTEMS LTD.
PRODUCT TECHNICAL DATA SHEET



XD
brochure [Download](#)



XD DOPs
and [Download](#)
certificates

Technical
characteristics

Application

Flue system/connecting
flue/renovation

Operating mode	Dry/wet
Pressure	Negative/positive pressure
Max. working pressure	200 Pa
Operating temperature	200°C positive pressure
600°C negative pressure	
Max. temperature allowed	1000°C (max 30 min)
material	AISI 316L/EN 1.4404
AISI 904L/EN 1.4539	
thickness	0.1 mm
Fuel type	Oil/Gas/Wood/Pellets Normal (Wood)