



Pumice T-Liner 45deg / 90deg



Suitable for use in negative pressure (Dry Chimney) applications. CE Designation (T450 N2 D 3 G)

Features Benefits

- Pumice Concrete
- Highly Insulated
- Lightweight
- Resistance to temperature changes
- Easy to Use
- Better performance

VARIATIONS

SKU	Int mm	Angle	Height	Price
126376	150	45	600	£145.20 ex. VAT
126500	175	45	600	£151.27 ex. VAT
127695	200	45	600	£157.41 ex. VAT
126375	150	90	600	£145.20 ex. VAT

For stove and chimney installers - whenever you register an installation with our easy to use, online guarantee registration portal, you will now accrue points based on the number of installations. So [click here](#) to start and register your installations, taking full advantage of our Lifetime Guarantee on Flex and ICID, as well as guarantees on all our other ranges, and to start earning points



[wprm_package id='47854']

Isokern Pumice Double Module DM is CE Certified to EN1858 TÜV Cert no. 0036 CPR 90219 001
Isokern Pumice Chimney Liner is CE certified to EN1857 TÜV Cert no. 0036 CPR 90219 002
Isokern Magnum Firechest has been tested at the Fraunhofer Institut, Stuttgart, Cert no. P8-094/2006

CE Designation

Double Module DM System Chimney* T450 N1 D 3 G(00)
Pumice Chimney Liner T600 N2 D 3 G

* Zero distance to combustibles on straight chimney systems with ventilated terminal. 38mm distance to combustibles on offset systems. and non ventilated systems.

[Isokern brochure](#)

[Magnum Firechest instructions](#)

[Click here](#) to view Certificates and Declarations of Performance for Isokern DM