



## Storm Collar Stainless Steel ICS50 - 5000



This product is part of Schiedel's accessory range which can be used on a variety of systems. Please consult with our customer service team for advice on its suitability.

Schiedel have a range of chimney and flue components suitable for all types of appliances, from wood stoves to CHP system and gas boiler system to data centre generators, and more.



Schiedel is the first European chimney manufacturer to have performed the tests according to this latest fire resistance standard for chimneys. European standard BS EN 1366-13:2019 "Fire resistance tests for service installations, Part 13: Chimneys" and has reached EI 120 classification for our Double Wall Insulated System Chimney ICS in a closed scenario (type A) for both vertical and horizontal set-ups.

ICS 5000 is tested and approved in both 25mm and 50mm variants to BS EN 1856-1 as a System Chimney and to BS EN 1856-2 as a connecting flue pipe with the following designations

### System Chimney BS EN 1856-1 (TÜV 0036 CPR 9195 027)

#### ICS25 5000

T600 H1 D V3 L50050 O75\* T200 H1 W V2 L50050 O50\*\*

#### \*Distance to Combustibles

\*Ø80-Ø300 distance – 75mm

\*Ø350-Ø450 distance – 112.5mm

\*Ø500- Ø600 distance – 150mm

\*\*Ø80-Ø200 distance – 50mm

#### ICS50 5000



T600 H1 D V3 L50050 O25\*

**\*Distance to Combustibles**

\*Ø80-Ø300 distance – 25mm

\*Ø350-Ø450 distance – 37.5mm

\*Ø500- Ø600 distance – 50mm

**Connecting Flue Pipe BS EN 1856-2 (TÜV 0036 CPR 9195 038)**

T600 H1 D V3 L50050 O100 M

**Connecting Flue Pipe BS EN 1856-2 (TÜV 0036 CPR 9195 036)**

T600 H1 D V3 L50050 O100 M

**EI 120 Fire rating to BS EN 1366-13 Chimneys**

ICS25 5000 and ICS50 5000: Horizontal and Vertical

**Corrosion testing on Gas, Oil, Solid Fuel (TÜV 0036 CPR 9195 027)**

Gastec, MPA, TÜV



ICS 5000  
brochure [Download](#)



ICS 5000  
installation [Download](#)  
instructions