



T CORBEL FOR EXTERNAL BRICKWORK - ISOKERN PUMICE



For DM Block Chimneys. Suitable for use in negative pressure (Dry Chimney) applications. CE Designation (T450 N1 D 3 G(00))

740mm T Corbel for external brickwork 75mm high

Features and Benefits

Leca Concrete ☑ Converts DM to brick stack

Reinforced with High Tensile Steel ☑ Fully load bearing

Holes for Reinforcement Rods ☑ Allows for tall stacks

VARIATIONS

SKU	Price	Size	A	B
130818		740	740	520

PRODUCT DESCRIPTION

Pumice is a natural insulator; this is the unique property that separates pumice from all other chimney material.

Schiedel Isokern is noteworthy for its flue and chimney products manufactured using high quality pumice which is recognised throughout Europe and USA.

SCHIEDEL ISOKERN OFFERS:

- The unique feature of Schiedel Isokern against other chimney systems is that pumice is known for its natural insulating properties.
- Pumice allows the flue gases in the chimney to quickly reach their optimum temperature enabling the heating appliance to reach its optimum performance shortly after lighting.
- It keeps the chimney warmer longer as the heat output of the appliance decreases, once again aiding performance and reducing the likelihood of condensation and soot build-up.
- ISOKERN is a well reputed brand known for its durability, reliability and long lasting, robust performance, under the Schiedel product portfolio.
- We have the Largest collection of masonry chimney & fire chest products
- Our products are CE marked
- Our products are tested to the appropriate EN standards



Isokern Pumice Double Module DM is CE Certified to EN1858 TÜV Cert no. 0036 CPR 90219 001
Isokern Pumice Chimney Liner is CE certified to EN1857 TÜV Cert no. 0036 CPR 90219 002
Isokern Magnum Firechest has been tested at the Fraunhofer Institut, Stuttgart, Cert no. P8-094/2006

CE Designation

Double Module DM System Chimney* T450 N1 D 3 G(00)
Pumice Chimney Liner T600 N2 D 3 G

* Zero distance to combustibles on straight chimney systems with ventilated terminal. 38mm distance to combustibles on offset systems. and non ventilated systems.



[Isokern Brochure](#)
File size 8.18 MB
[Download](#)



[Garden Fireplace 500 build guide](#)
File size 23.88 MB
[Download](#)



[Garden Fireplace 950 build guide](#)
File size 3.38 MB
[Download](#)



[Garden Fireplace 1200 build guide](#)
File size 4.04 MB
[Download](#)



[Celsius stove brochure](#)
File size 1.25 MB
[Download](#)



[Isokern Pumice bends DWG files](#)
File size 3.19 MB
[Download](#)



[Manor Gather DWG files](#)
File size 4.42 MB
[Download](#)

A useful app with guides on installation as well as step-by-step video guides.

This app was designed for installers to have all the information they require in a few quick clicks. This makes it easier for installers rather than having to carry paperwork during the installation process with video breakdowns of each stage of the installation process.

Download the iPhone and iPad version in the App Store and Android version in the Google Play Store.

