



## TecnoFlex Cradle and Boat 904L



### TecnoFlex has a number of features:

- Unique joint design giving exceptional strength to the lock.
- Both inner and outer layers made from corrosion-resistant 904L stainless steel.
- Corrugated outer skin for high crush resistance.
- Extra smooth inner skin allows for easy drain down of condensates, less opportunity for soot to collect in the joint area and ease of sweeping.
- Inner skin remains smooth and protective even after the rigours of installation.

### VARIATIONS

SKU	Int mm	Length	Steel	Price
125449	125	80	904	
126471	155	60	904	
154658	180	40	904	
154659	200	30	904	

### PRODUCT DESCRIPTION

#### Flexible Flue Twin Wall Liner

TecnoFlex Plus is a twin skin flexible chimney liner designed for gas, oil and multi-fuel, where the maximum flue gas temperature does not exceed 600°C. Diameter range 80 - 300mm. Flex Liners come with a Lifetime Guarantee\*

- Corrugated outer skin for high crush resistance.
- Extra smooth inner skin allows for easy drain down of condensates, less opportunity for soot to collect in the joint area and ease of sweeping.



- Engineered joint design gives extra strength and flexibility.
- Inner skin remains smooth and protective even after the rigours of installation.
- Now with Lifetime\*Guarantee.



For stove and chimney installers – whenever you register an installation with our easy to use, online guarantee registration portal, you will now accrue points based on the number of installations and installation type. So start to register your installations, taking full advantage of our Lifetime Guarantee on Flex and ICID, as well as guarantees on all our other ranges, and to start earning points



[TecnoFlex  
DOPs and  
certificates](#) [Download](#)



[Triplelock  
DOPs and  
certificates](#) [Download](#)



[XD DOPs  
and  
certificates](#) [Download](#)

**TecnoFlex  
Plus is CE  
Certified to  
BS  
EN1856-2  
TÜV 0036  
CPR 9195  
035 with  
designations:**

#### High Temperature Applications

T600 N1 W V2 L50012 G

T600 N1 W V2 L70012 G

#### Low Temperature Applications

T200 P1 W V2 L50012 O

T200 P1 W V2 L70012 O

**Triplelock Plus is CE Certified to BS EN1856-2 TÜV 0036 CPR 9195 043 with designations:**

#### Applications

T300 N1 W V2 L50010 O



[Flexible  
Liners  
brochure](#) [Download](#)



[Flexible  
Liners  
installation  
instructions](#) [Download](#)

**A useful app with guides on installation as well as step-by-step video guides.**

This app was designed for installers to have all the information they require in a few quick clicks. This makes it easier for installers



**SCHIEDEL CHIMNEY SYSTEMS LTD.  
PRODUCT TECHNICAL DATA SHEET**



rather than having to carry paperwork during the installation process with video breakdowns of each stage of the installation process.

Download the iPhone and iPad version in the App Store and Android version in the Google Play Store.

