


# SCHIEDEL CHIMNEY SYSTEMS LTD. PRODUCT TECHNICAL DATA SHEET



### Top Clamp - Flexible Liners





This item is used in conjunction with the Top Plate to secure the liner at the top of the stack. It can also be used as an intermediate support.

### **Features and Benefits**

Round shape → Clamps around pipe lengths

316L stainless steel → Corrosion-resistant.

Smooth finish → Provides a more safe, neat finish to the flexible liner.

Lightweight → Easy to install

### **VARIATIONS**

SKU	Int mm	Colour	Price
106937	080	Plain	
106938	100	Plain	
125116	125	Plain	
126427	155	Plain	
106945	180	Plain	
106946	200	Plain	
106947	230	Plain	
106948	250	Plain	
106949	300	Plain	

### **PRODUCT DESCRIPTION**

TecnoFlex Plus is a twin skin flexible chimney liner designed for gas, oil and multi-fuel, where the maximum flue gas temperature does not exceed 600°C. Diameter range 80 - 300mm. Flex Liners come with a Lifetime Guarantee\*



# SCHIEDEL CHIMNEY SYSTEMS LTD. PRODUCT TECHNICAL DATA SHEET



#### Flexible Flue Twin Wall Liner

- Corrugated outer skin for high crush resistance.
- Extra smooth inner skin allows for easy drain down of condensates, less opportunity for soot to collect in the joint area and ease of sweeping.
- Engineered joint design gives extra strength and flexibility.
- Inner skin remains smooth and protective even after the rigours of installation.
- Now with Lifetime\*Guarantee.

Triplelock Plus is a single wall stainless steel flexible flue liner designed for atmospheric gas and kerosene appliances where the flue gas temperature does not exceed 260°C. Diameter range Triplelock plus 100 - 200mm.


### Flexible Flue Single Wall Liner


- Made from corrosion-resistant 316L stainless steel. Leak resistant construction due to dovetail folded seam.
- Deep corrugations for high crush resistance and better flexibility when installing.
- Strong seam construction resists the rigours of pulling the liner into place during construction.



For stove and chimney installers – whenever you register an installation with our easy to use, online guarantee registration portal, you will now accrue points based on the number of installations and installation type. So start to register your installations, taking full advantage of our Lifetime Guarantee on Flex and ICID, as well as guarantees on all our other ranges, and to start earning points







TecnoFlex Plus is CE Certified to BS EN1856-2 TÜV 0036 CPR 9195 035 with designation s:

High Temperature Applications T600 N1 W V2 L50012 G T600 N1 W V2 L70012 G

Low Temperature Applications T200 P1 W V2 L50012 O T200 P1 W V2 L70012 O

Triplelock Plus is CE Certified to BS EN1856-2 TÜV 0036 CPR 9195 043 with designations:



# SCHIEDEL CHIMNEY SYSTEMS LTD. PRODUCT TECHNICAL DATA SHEET



### Applications T300 N1 W V2 L50010 O



A useful app with guides on installation as well as step-by-step video guides.

This app was designed for installers to have all the information they require in a few quick clicks. This makes it easier for installers rather than having to carry paperwork during the installation process with video breakdowns of each stage of the installation process.

Download the iPhone and iPad version in the App Store and Android version in the Google Play Store.



