




Vantage Storm collars and flashings



Stocks available. Please contact us on 0191 4161150 or email sales.uk@schiedel.com to purchase this product. List pricing is shown below.

Download the brochure for dimensions and other details.

 Vantage Twin Wall Flue Download	1	STORMCOLLAR 125/40/0.5/304/BA/EX	
	6		
	5		
	5		
	4		
5			
165546		STORMCOLLAR 125/40/0.5/304/BLACK/EX	7.28
165547		STORMCOLLAR 150/40/0.5/304/BA/EX	6.20
165548		STORMCOLLAR 150/40/0.5/304/BLACK/EX	7.74
165549		STORMCOLLAR 175/40/0.5/304/BA/EX	6.27
165550		STORMCOLLAR 175/40/0.5/304/BLACK/EX	7.84



SCHIEDEL CHIMNEY SYSTEMS LTD.
PRODUCT TECHNICAL DATA SHEET



165551	STORMCOLLAR 200/40/0.5/304/BA/EX	7.16
165552	STORMCOLLAR 200/40/0.5/304/BLACK/EX	8.96
165553	ROOF_FLASH /125/5-30/0.5/304/BA/EX	10.67
165554	ROOF_FLASH /125/5-30/0.5/304/BLACK/EX	13.34
165555	ROOF_FLASH /150/5-30/0.5/304/BA/EX	10.88
165556	ROOF_FLASH /150/5-30/0.5/304/BLACK/EX	13.61
165557	ROOF_FLASH /175/5-30/0.5/304/BA/EX	12.45
165558	ROOF_FLASH /200/5-30/0.5/304/BA/EX	13.20

Vantage is a quality twin wall chimney system with a quick lock jointing system. It is used for wood burning or for solid fuel stoves.



With a quick lock jointing system. The components have a twin wall construction with a male spigot and a female socket to provide simple and rapid installation.

With its fully sealed components, Vantage can be installed both internally and externally. Vantage is supplied with a ten year conditional warranty.

PRODUCT DESCRIPTION

Applications

- Gas-fired stoves
- Wood-fired stoves
- Approved solid fuels
- Oil-fired appliances

Key features

- 10 year warranty
- Suitable for internal and external applications Distance to combustibles 60mm (50mm in free air)
- Also available in black powder coated finish
- Easy to install Twist-lock system Weatherproof, fully sealed components High density, mineral wool insulation Made from high grade stainless steel
- 316L stainless steel inner wall for the highest corrosion resistance
- 304 stainless steel outer wall in an attractive, polished finish

Technical characteristics				
Application		Chimney/Flue system		
Operating mode		Dry		
Pressure		Negative pressure		
Operating Temperature		450 oC / 600 oC		
Thermal Shock		1000 oC [max 30 min]		
Inner Wall	material	AISI 316L/EN 1.4404		
	thickness	0.5 mm		
Outer wall	material	AISI 304 BA/EN 1.4301		
	thickness	0.5 mm		
Insulation	type	Mineral wool		
	thickness	25 mm		
Fuel Type		Wood/Gas/Oil/Approved Solid Fuels		
ID mm	125(5")	150(6")	175(7")	200(8")
OD mm	175		200	230 250
Cross section cm2	123		177	241 314
Weight ±kg/m	5.5		6.5	7.5 8.0
Chimney diameter				
The chimney size should be as recommended by the appliance manufacturer. Where there is a requirement for a flue diameter smaller than the appliance spigot, then the operational requirements of the appliance and the configuration of the flue must satisfy the flue sizing requirements of EN13384—1 for single appliances.				



SCHIEDEL CHIMNEY SYSTEMS LTD.
PRODUCT TECHNICAL DATA SHEET



CE approved

EN1856: T450 N1 D V3 L50050 G50 [in free air]

EN1856: T450 N1 D V3 L50050 G60 [in a combustibile shaft with ventilated fire stops]

EN1856: T600 N1 D V3 L50050 G100 [in a combustibile shaft with ventilated fire stops]