



## XD CRADLE AND BOAT 316L



### VARIATIONS

SKU	Price	Int mm	Length	Steel
168712		150	60	316
168711		125	80	316



Metaloterm

XD  
brochure

[Download](#)

#### Technical characteristics

Application	Flue system/connecting flue/renovation
Operating mode	Dry/wet
Pressure	Negative/positive pressure
Max. working pressure	200 Pa
Operating temperature	200°C positive pressure
600°C negative pressure	
Max. temperature allowed	1000°C (max 30 min)
material	AISI 316L/EN 1.4404
AISI 904L/EN 1.4539	
thickness	0.1 mm
Fuel type	Oil/Gas/Wood/Pellets Normal (Wood)



TecnoFlex Plus is CE Certified to BS EN1856-2 TÜV 0036 CPR 9195 035 with designations:

#### High Temperature Applications

T600 N1 W V2 L50012 G

T600 N1 W V2 L70012 G

#### Low Temperature Applications

T200 P1 W V2 L50012 O

T200 P1 W V2 L70012 O

Triplelock Plus is CE Certified to BS EN1856-2 TÜV 0036 CPR 9195 043 with designations:

#### Applications

T300 N1 W V2 L50010 O



[Flexible  
Liners  
brochure](#) [Download](#)



[Flexible  
Liners  
installation  
instructions](#) [Download](#)

**A useful app with guides on installation as well as step-by-step video guides.**

This app was designed for installers to have all the information they require in a few quick clicks. This makes it easier for installers rather than having to carry paperwork during the installation process with video breakdowns of each stage of the installation process.

Download the iPhone and iPad version in the App Store and Android version in the Google Play Store.

